

Power Cell DIESEL GENERATOR

Cummins Series
Diesel Generator Set/50Hz
600KVA



Features

- » Compact structure with high-strength chassis;
- » Easy operation and maintenance, low cost;
- » Excellent performance damping
- » Compliance with international electrical safety standards of electrical
- » 8 hours base tank;
- » High-performance maintenance-free batteries with isolation switch;
- » 50°C Radiator;
- » Forklift bottom hole design, easy to transport;
- » Industrial muffler;
- » Noise reduction structure, low noise;
- » Convenient power output interface;
- » IP56(control system);
- » Customized design for user;

Power Cell DIESEL GENERATOR

Technical Data

| Model | CU600 | | Alternator | |
|---------------------------|-----------------------|---------|--|---------------------------|
| Prime power | kW | 480.0 | Model | ZL354F |
| | kVA | 600.0 | Phase | 3.0 |
| Standby power | kW | 528.0 | Voltage | 400/230 |
| | kVA | 660.0 | Wiring type | 3 Phase 4 wire |
| Rated voltage | V | 400/230 | Bearing | 1 |
| Rated current | A | 866 | Power factor | 0.8 |
| Sound level | dB(@7m) | ≤72 | Frequency | Hz |
| | | | | 50 |
| Engine | | | Prime power | kW |
| Brand | Cummins | | 480 | |
| Model | KTAA19-G6A | | Exciter type | Brushless,self-excitation |
| Aspiration | Turbo,Air/Air Cooling | | Voltage regulation | % |
| No. of cylinder | 6 | | Protection grade | IP23 |
| Fuel injection system | PT type | | Insulation grade | H/H |
| Displacement | Liquid | 18.9 | Altitude | m |
| Bore/Stroke | mm | 159*159 | | ≤1000 |
| Compression ratio | | 13.5 | Controller | |
| Rated speed | rpm | 1500 | Brand | DeepSea |
| Rated power | kW | 555 | Model | DSE6120 |
| Governing method | EFC Electrical | | <ul style="list-style-type: none"> ● Generator & load power monitoring (kW, kV A, kV Ar, pf) ● Generator overload protection (kW) ● Generator/load current monitoring & protection ● Configurable analogue/digital inputs ● Configurable DC, volt-free and staged loading outputs ● CAN, MPU & alternator speed sensing ● Tier 4 CAN engine support ● Configurable event log (50) ● DSE Configuration Suite PC Software ● Fuel and start outputs (configurable on CAN) | |
| Starting Motor | V | 24 | | |
| Exhause System | | | | |
| Exhause gas flow | L/s | 1992 | | |
| Exhause gas temp | °C | 490 | | |
| Max back pressure | kPa | 10 | | |
| Air Intake System | | | | |
| Max intake restrictio | kPa | 6.23 | | |
| Consumption | L/s | 750 | | |
| Air flow | L/s | 10800 | | |
| Fuel System | | | | |
| 100% load | L/h | 113 | | |
| 75% load | L/h | 91 | | |
| 50% load | L/h | 61 | | |
| Fuel tank capacity | L | 700 | | |
| Lubrication System | | | | |
| Oil capacity | L | 50 | Dimension and Weight | |
| Oil consumption | g/kw.h | ≤4 | Open type | Silent type |
| Min oil pressure | kPa | 345-483 | Model | EP-CU600 |
| Cooling System | | | Length(L) (mm) | 3600 |
| Coolant capacity | L | 116.5 | Width(W) (mm) | 1600 |
| Thermostat | °C | 82-94 | Height(H) (mm) | 2250 |
| Top tank temperatur | °C | 104 | Weight (kgs) | 4300 |
| | | | | 5300 |



Dimension and Weight