

Power Cell DIESEL GENERATOR

Cummins Series
Diesel Generator Set/50Hz
750KVA



Features

- » Compact structure with high-strength chassis;
- » Easy operation and maintenance, low cost;
- » Excellent performance damping
- » Compliance with international electrical safety standards of electrical
- » 8 hours base tank;
- » High-performance maintenance-free batteries with isolation switch;
- » 50°C Radiator;
- » Forklift bottom hole design, easy to transport;
- » Industrial muffler;
- » Noise reduction structure, low noise;
- » Convenient power output interface;
- » IP56(control system);
- » Customized design for user;



Power Cell DIESEL GENERATOR

Technical Data

Model		CU750
Prime power	kW	600.0
	kVA	750.0
Standby power	kW	660.0
	kVA	825.0
Rated voltage	V	400/230
Rated current	A	1083
Sound level	dB(@7m)	≤72

Engine

Brand	Cummins	
Model	KTA38-G2	
Aspiration	Turbo,Air/Water Cooling	
No. of cylinder	V12	
Fuel injection system	PT type	
Displacement	Liquid	37.8
Bore/Stroke	mm	159*159
Compression ratio	14.5	
Rated speed	rpm	1500
Rated power	kW	664
Governing method	EFC Electrical	
Starting Motor	V	24

Exhaust System

Exhaust gas flow	L/s	2634
Exhaust gas temp	°C	552
Max back pressure	kPa	10

Air Intake System

Max intake restrictio	kPa	6.23
Consumption	L/s	920
Air flow	L/s	30425

Fuel System

100% load	L/h	150
75% load	L/h	112.5
50% load	L/h	76
Fuel tank capacity	L	1000

Lubrication System

Oil capacity	L	135
Oil consumption	g/kw.h	≤4
Min oil pressure	kPa	310-448

Cooling System

Coolant capacity	L	252
Thermostat	°C	82-93
Top tank temperatur	°C	104

Alternator

Model	STAMFORD	LVI634B
Phase	3.0	
Voltage	V	400/230
Wiring type	3 Phase 4 wire	
Bearing	1	
Power factor	0.8	
Frequency	Hz	50
Prime power	kW	600
Exciter type	Brushless,self-excitation	
Voltage regulation	%	±0.5
Protection grade	IP23	
Insulation grade	H/H	
Altitude	m	≤1000

Controller

Brand	DeepSea
Model	DSE6020

- Generator & load power monitoring (kW, kV A, kV Ar, pf)
- Generator overload protection (kW)
- Generator/load current monitoring & protection
- Configurable analogue/digital inputs
- Configurable DC, volt-free and staged loading outputs
- CAN, MPU & alternator speed sensing
- Tier 4 CAN engine support
- Configurable event log (50)
- DSE Configuration Suite PC Software
- Fuel and start outputs (configurable on CAN)



Dimension and Weight

	Open type	Silent type
Model	EP-CU750	EPS-CU750
Length(L) (mm)	4450	6058
Width(W) (mm)	1750	2438
Height(H) (mm)	2430	2591
Weight (kgs)	6950	11500